

Thermophysical Properties and Structure Evolution of Mechanically Activated BaTiO₃

V. P. Pavlovic

Faculty of Mechanical Engineering, Kraljice Marije 16, 11000 Beograd, Serbia and Montenegro

M. V. Nikolic

*Center for Multidisciplinary Studies of the University of Belgrade, Kneza Visaslava 1, 11000
Belgrade, Serbia and Montenegro*

V. B. Pavlovic

Faculty of Agriculture, University of Belgrade, 11000 Beograd, Serbia and Montenegro

L. Lukic^S

IRITEL, Batajnicksi put 23, 11000 Belgrade, Serbia and Montenegro

P. M. Nikolic^C M. M. Ristic

*Institute of Technical Sciences of SASA, Knez Mihailova 35/IV, 11000 Belgrade, Serbia and
Montenegro
nikolic@sanu.ac.yu*

It is well known that mechanical activation is often used for modification of physico-chemical properties of sintered materials. As a result of this process disordering of the crystal structure, plastic deformation of the powder particles and generation of different structural defects may occur, thus changing the final thermophysical properties of a sintered material. Having this in mind, thermophysical properties and structure evolution of mechanically activated BaTiO₃ was investigated in this paper. Investigations were carried out on high purity BaTiO₃ that was mechanically activated in a planetary ball mill in a continual regime up to 120 minutes and sintered up to 1380°C. Thermophysical properties of mechanically activated BaTiO₃ were investigated by the photoacoustic method, while structure investigations were carried out using scanning electron microscopy (SEM) and the X-ray powder diffraction method. The values of thermal diffusivity calculated from obtained photoacoustic spectra were a function of the mechanical activation time and sintering temperature and were between $0.32 \cdot 10^{-6}$ and $0.26 \cdot 10^{-5}$ m²/s. The results obtained enabled establishment of sintering parameters indispensable for processing materials with required properties.